

DECLARATION OF PERFORMANCE

No 1/05/2019

1. Manufacturer:

CONECTO Sp. z o.o.
ul. Przemysłowa 39
61-541 Poznań

2. Name of product:

Waterproofing expansion joints CONECTO PARK SL (EPDM, aluminium 6063) and CONECTO PARK GA (EPDM, stainless steel 1.4301, aluminium 6063)

3. Product class:

PKWiU 28.11.23-76.39

4. Intended use:

Waterproofing expansion joints CONECTO PARK SL and CONECTO PARK GA are used to waterproofing cover of expansion gap in floors inside and outside.

5. Referenced documents:

National Technical Assessment ITB-KOT-2019/0715 from 27.03.2019r.

6. Declared performance:

a) EPDM

- Shore's hardness 70±5 Sh (PN-EN ISO 868:2005)
- Stretching resistance ≥10MPa (PN-ISO 37:2007)
- Relative prolongation ≥400% (PN-ISO 37:2007)
- Permanent strain after 24h in temp. +70C ≤60% (PN-ISO 815-1998)
- Rending resistance ≥40N/mm (PN-ISO 34-1:2007)
- Liquid resistance:
 - Water – mass change ≤12%, thickness change ≤5% (PN-ISO 1817:2001)
 - Brine (saturated water mix with NaCl) – mass change ≤12%, thickness change ≤5% (PN-ISO 1817:2001)
 - Engine oil (Stell Heli Ultra 5W-40) – mass change ≤12%, thickness change ≤5% (PN-ISO 1817:2001)

b) Stainless steel 1.4301 – according to PN-EN 10088-4:2010

c) Aluminium 6063 – according to PN-EN 573-3, PN-EN 12020-1, PN-EN 15088

7. Name and number of certificated institute and number of certificate:

Instytut Techniki Budowlanej, ul. Filtrowa 1, 00-611 Warsaw, accreditation no. AB 023

I declare with the fully responsibility that product is accordant with documents listed in 5

Poznań, 15.05.2019r.
CEO Radosław Ole